ACM Email Room

Participant Linux Setup – Redhat 5.1 or later

1. Write down all your current settings in the spaces below. You will need this information when you go home. If you wish to create an alternate ACM profile so that you can switch back to your previous settings automatically, please ask the staff person for supplemental instructions.
2. Log in as root and type in 'linuxconf'.
3. Under Configuration, go to Networking and then select Client Tasks and Basic Host Information.
4. Under Adapter 1, the 'Config mode' should be set to manual. Insert the IP address and subnet mask numbers given below. Click Accept.
5. Under Client Tasks and Name Server Specification, insert the ACM Nameservers. Click Accept.
6. Under Routing and Gateways, click Defaults and enter the ACM gateway under 'Default gateway'. Do NOT enable Routing. Click Accept.

Number	Original	ACM
IP	___.___.___.___	132.236.46.___
Subnet mask	___.___.___.___	255.255.255.0
Default Gateway	___.___.___.___	132.236.46.1
Nameservers	___.___.___.___	128.84.242.46
	___.___.___.___	128.35.82.50
	___.___.___.___	
	___.___.___.___	

7. Under Control and Control Panel, click Activate Configuration. Click 'Activate Changes' and then click Quit. Keep these settings for the duration of the conference.
8. You may now plug into the ACM net on any available cable in the email room. The room is open from 8 AM to 6:30 PM each day.